

AMENDMENTS TO THE CLAIMS

1. (previously amended) An adjustable wreath hanger comprising:

an elongated hanger strip having an upper end comprising a rearwardly facing, resilient door hook and a downwardly extending portion having a plurality of vertically separated, forwardly facing detent members; and

an elongated hook strip having a lower end comprising a forwardly facing hook member, and upper portion comprising a resilient engagement tab having a rearwardly facing projection, a slide member attached to and cooperating with the upper portion of the hook strip to define an aperture thorough which the downwardly extending portion of the hanger strip is insertable to create an interfering fit between the rearwardly facing projection and the detent members, the slide member further comprising an upwardly extending, resilient backing tab spaced apart from the rearwardly facing projection, the backing tab biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.

2. (original) The adjustable wreath hanger of claim 1 wherein the rearwardly facing projection and the detent members are shaped so as to enable the rearwardly facing projection to override the detent members whenever the hook strip slides upwardly relative to the hanger strip.

3. (original) The adjustable wreath hanger of claim 1 wherein the backing tab has a top end with a forwardly extending projection that biases the detent member of the hanger strip against the rearwardly facing projection to prevent the hook strip from sliding downwardly in relation to the hanger strip.

4. (original) The adjustable wreath hanger of claim 3 wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the application of a rearwardly directed force to the hanger strip at a point above the top of the backing tab.

5. (original) The adjustable wreath hanger of claim 1 wherein the rearwardly facing projection is a molded plastic tooth.

6. (original) The adjustable wreath hanger of claim 1 wherein the hanger strip and the hook strip are molded from polycarbonate resin.

7. (new) The adjustable wreath hanger of claim 1 wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the simultaneous application of a forwardly directed force to the adjustable engagement tab and a rearwardly directed force to the backing tab, thereby enabling the free movement of the hook strip in an upward or downward direction.

8. (new) The adjustable wreath hanger of claim 1 wherein the backing tab has a top end with a projection that biases the hanger strip into cooperative alignment with the hook strip when the hook is under load.

9. (new) An adjustable wreath hanger comprising:

an elongated hanger strip having an upper end comprising a rearwardly facing, resilient door hanger and a downwardly extending portion having a plurality of vertically separated detent members disposed on the forward surface of the hanger strip; and

an elongated hook strip having a lower end comprising a forwardly facing hook member, and an upper portion comprising a resilient engagement tab having a rearwardly facing projection, and further comprising a slide member that defines an aperture thorough which the downwardly extending portion of the hanger strip is insertable to align the hanger strip with the hook strip and to create an interfering fit between the rearwardly facing projection and the detent members, the slide member further comprising a resilient backing tab opposing the rearwardly facing projection, the backing tab biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.

10. (new) An adjustable wreath hanger comprising:

an elongated hanger strip having an upper end comprising a rearwardly facing, resilient door hanger and a downwardly extending portion having a plurality of vertically separated, detent members disposed on the forward surface of the hanger strip; and

an elongated hook strip having a lower end comprising a forwardly facing hook member, and upper portion comprising a resilient engagement tab having a rearwardly facing projection, and further comprising a slide member that defines an aperture thorough which the downwardly extending portion of the hanger strip is insertable to create an interfering fit between the

rearwardly facing projection and the detent members, the slide member further comprising a resilient backing tab opposing the rearwardly facing projection, wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the simultaneous application of a forwardly directed force to the adjustable engagement tab and a rearwardly directed force to the backing tab, thereby enabling the free movement of the hook strip in an upward or downward direction, the backing tab having a projection that biases the detent member of the hanger strip against the rearwardly facing projection to keep the hook strip and the hanger strip cooperatively aligned when the hook is under load, and biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.

11. (new) An adjustable wreath hanger comprising:

a hanger strip comprising a top portion, an elongated first downwardly-extending portion attached at its first end to a first end of the top portion and arranged at a right angle relative to the top portion, the first downwardly extending portion having at its second end a plurality of vertically separated, detent members disposed on the forward-facing surface of the hanger strip, and a second downwardly-extending, rearwardly-facing portion opposing the first downwardly extending portion, and comprising a resilient member attached at its first end to a second end of the top portion, and arranged at an angle from about 90 degrees to 75.8 degrees relative to the top portion; and

an elongated hook strip having a lower end comprising a forwardly facing hook member, and an upper portion comprising a resilient engagement tab having a rearwardly facing projection, and further comprising a slide member that defines an aperture thorough which the downwardly extending portion of the hanger strip is insertable to align the hanger strip with the hook strip and to create an interfering fit between the rearwardly facing projection and the detent members, the slide member further comprising a resilient backing tab opposing the rearwardly facing projection, the backing tab biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.

12. (new) The adjustable wreath hanger of claim 9, wherein said door hanger can be mounted over a door such that the top portion rests on the top of the door, the first downwardly extending portion rests substantially flat on one face of the door, and the second downwardly extending portion opposes said first downwardly extending portion on an opposite face of the door, and adjustably flexes to about 90 degrees relative to the top portion to accommodate doors of various thicknesses.

13. (new) The adjustable wreath hanger of claim 10, wherein the second end of the second downwardly-extending portion comprises a rearwardly-facing hook member.

14. (new) A wreath hanger comprising

a top portion, and an elongated, first downwardly-extending portion attached at its first end to a first end of the top portion and arranged at a right angle relative to the top portion, and having at its second end a forwardly facing hook member, and a second downwardly-extending, rearwardly-facing portion opposing the first downwardly extending portion, and comprising a resilient member attached at its first end to a second end of the top portion, and arranged at an angle from about 90 degrees to 75.8 degrees relative to the top portion.

15. (new) The wreath hanger of claim 14, wherein said door hanger can be mounted over a door such that the top portion rests on the top of the door, the elongated first downwardly extending portion rests substantially flat on one face of the door, and the second downwardly extending portion opposes said first downwardly extending portion on an opposite face of the door, and adjustably flexes to about 90 degrees relative to the top portion to accommodate doors of various thicknesses.

16. (new) The wreath hanger of claim 14 wherein the second end of the second downwardly-extending portion comprises a rearwardly-facing hook member.

17. (new) An adjustable wreath hanger comprising:

an elongated hanger strip having an upper end comprising a rearwardly facing, resilient door hook and a downwardly extending portion having a plurality of vertically separated, forwardly facing detent members; and

an elongated hook strip having a lower end comprising a forwardly facing hook member, and upper portion comprising a resilient engagement tab having a rearwardly facing projection, a

slide member attached to and cooperating with the upper portion of the hook strip to define an aperture thorough which the downwardly extending portion of the hanger strip is insertable to create an interfering fit between the rearwardly facing projection and the detent members, the slide member further comprising an upwardly extending, resilient backing tab spaced apart from the rearwardly facing projection, the backing tab biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use, and wherein the backing tab has a top end with a forwardly extending projection that biases the detent member of the hanger strip against the rearwardly facing projection to prevent the hook strip from sliding downwardly in relation to the hanger strip, and wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the application of a rearwardly directed force to the hanger strip at a point above the top of the backing tab.